


TABULKA NOSNOTÍ ŘETEZOVÝCH VAZÁKŮ tř.8



Způsob vázání

Přímý

Přímý

Přímý

Na smyčku

Na smyčku

Opásáním

Opásáním

Věncové

Úhel sklonu	0°	$\beta \leq 45^\circ$	$\beta \leq 60^\circ$	$\beta \leq 45^\circ$	$\beta \leq 60^\circ$	0°	$\beta \leq 45^\circ$	$\beta \leq 60^\circ$	$0^\circ \leq \beta \leq 45^\circ$	$0^\circ \leq \beta \leq 45^\circ$	0°
Zátěžový faktor	1	1,4	1	2,1	1,5	0,8	1,12	0,8	1,4	2,1	1,6
Ø Řetězu	Nosnost (kg)										
6	1120	1600	1120	2360	1700	900	1260	900	1600	2360	1800
7	1500	2120	1500	3150	2240	1200	1680	1200	2120	3150	2500
8	2000	2800	2000	4250	3000	1600	2240	1600	2800	4250	3150
10	3150	4250	3150	6700	4750	2520	3530	2520	4250	6700	5000
13	5300	7500	5300	11200	8000	4240	5940	4240	7500	11200	8500
16	8000	11200	8000	17000	11800	6400	8960	6400	11200	17000	12500
18	10000	14000	10000	21200	15000	8000	11200	8000	14000	21200	16000
20	12500	17000	12500	26500	19000	10000	14000	10000	17000	26500	20000
22	15000	21200	15000	31500	22400	12000	16800	12000	21200	31500	23600
26	21200	30000	21200	45000	31500	17000	23700	17000	30000	45000	33500
32	31500	45000	31500	67000	47500	25200	35300	25200	45000	67000	50000



GANAS spol.s r. o.

Areál Svit budova č. 57
762 02 Zlín

E-shop: www.vazaky.com

e-mail: info@vazaky.com

www.ganas-jeraby.cz



737 540 392

577 522 512

577 523 136

